



Spire II Series – Cold Wide Format Professional Laminators



The GBC Spire II 54C and 64C take cold laminating to a new level. These mid-range machines feature sleek yet durable all steel design and capabilities often found in higher priced laminators. Created to protect heat sensitive media, the Spire II 54C and 64C promise improved productivity, versatility and quality – all at a great price.

With running speeds up to 15 feet per minute and up to 1-3/8" mounting capabilities, the Spire II 54C and 64C keep productivity at the forefront while ensuring the versatility needed to meet ever-changing market demands.

Features and benefits

Easy to Use

- Simple, intuitive control panel with LED pressure readout
- Variety of speed adjustments for operator comfort
- Removable front feed table and fixed rear output table facilitates roll changing and feeding
- Reversible motor clears feed jams

Productive

- 15ft/min laminating capability
- Foot pedal for hands-free operation

Versatile

- Up to 54" or 64" wide laminating and mounting capabilities
- Increased mounting gap allows for mounting to thicker substrates
- Larger film rolls can load easily on the machine

Durable

- All steel construction for lasting performance



Spire II Series – Cold Wide Format Professional Laminators

Spire II 54C and 64C Specifications

Item number	54C – 1737173 64C – 1737181
Maximum Laminating Width	54C – 54" 64C – 64"
Unwinds / Rewinds	Top - 1 Unwind, 1 Rewind Bottom Front - 1 Multicore Media Unwind Lower Rear - 1 Optional Rewind
Maximum Speed	15 ft./min. — Variable
Nip Roller Diameter	4"
Maximum Mounting Gap	1-3/8"
Type of Roller Pressure Adjust.	Infinite crank handle with scale indicator for gap and LED pressure readout
Protective Shield (Main Rollers)	Photo Eye
Foot Switch	Yes
Type of Supply Shafts	2 Drop-In Autogrip 1 Drop-In Multicore Media Additional Autogrip and Multicore Media Available
Maximum Film Outside Diameter	8.5"
Digital Keypad	Yes
Front and Rear Feed Tables	Front, Removable Pivot-up, Front and Rear table Idler bars - Optional Rear, Fixed
Drive System	Sprocket & Chain
Rear Cut Off	Optional
Roll-to-Roll Capabilities	Optional
Available Stand	Standard
Weight, lbs.	Net: 54C – 497 lbs., 64C – 550 lbs. Shipping: 54C – 607 lbs., 64C – 704 lbs.
Dimensions: in. (w x l x h)	Net: 54C – 71.1" x 27" x 52.6, 64C – 80.9" x 27" x 52.6 Shipping: 54C – 74.2" x 30.1" x 59.6", 64C – 85.2" x 30.1" x 59.6
Voltage/Amperage	115 VAC, 2 Amps (NEMA 5-15)

Films

For best results use high-quality GBC[®] films and mounting adhesives

- Arctic[®] Pressure Sensitive Films
- Arctic[®] Mounting Adhesives