



Spire III Series – Cold Wide Format Professional Laminators



Spire III 64Ct takes cold laminating to a new level. The top of the line machine features sleek yet durable, all steel design and capabilities found in only premium machines. Created to protect heat sensitive media and equipped with top heat assist for the best quality output, the Spire III 64Ct promises improved productivity, versatility and quality – all at a great price. Featuring runs speeds up to 20 feet per minute and 2" mounting capabilities, the Spire III 64Ct makes laminating and mounting displays, tradeshow graphics and easier than ever.

Features and benefits

Easy to Use

- Simple, intuitive control panel with LED pressure readout
- Infinite adjustments for operator comfort
- Swing-up front feed table and extra large fixed rear output table facilitates roll changing and feeding
- Reversible motor clears feed jams

Productive

- 20ft/min laminating capability
- Roll-to-roll capabilities
- Foot pedal for hands-free operation
- Top heat assist reduces curing times

Versatile

- Up to 64" wide laminating and mounting capabilities
- 4 unwind/rewind supply shafts
- Increased mounting gap allows mounting to thicker substrates
- Larger film rolls can load easily on the machine
- Optional unwind and rewind

Durable

- All steel construction for lasting performance



Spire III Series – Cold Wide Format Professional Laminators

Spire III 64Ct Specifications

Item Number	1737176
Maximum Laminating Width	64"
Unwinds / Rewinds	Top - 1 Unwind, 1 Rewind Bottom Front - 1 Unwind, 1 Optional Unwind Top Rear - Optional Rewind Lower Rear - 1 Rewind
Maximum Speed	20 ft./min., Variable
Nip Roller Diameter	4"
Maximum Mounting Gap	2"
Type of Roller Pressure Adjust.	Infinite cranks handle with scale indicator for gap and LED pressure readout
Protective Shield (Main Rollers)	Photo Eye
Foot Switch	Yes
Type of Supply Shafts	2 Drop-In Autogrip 2 Drop-In Multicore Media Additional Autogrip and Multicore Media Available
Maximum Film Outside Diameter	10"
Digital Keypad	Yes
Front Feed Table	Swing Up
Drive System	Sprocket & Chain
Rear Cut Off	Optional
Roll-to-Roll Capabilities	Yes
Available Stand	Standard
Weight, lbs.	Net: 803 lbs. Shipping: 1,067 lbs.
Dimensions: in. (w x l x h)	Net: 81.2" x 31.5" x 55.9" Shipping: 81.9" x 32.1" x 62.2"
Voltage/Amperage	115 VAC, 12 Amp (NEMA 5-15)

Applications

- Window graphics
- Trade show displays
- POP displays
- Rigid displays
- Floor graphics
- Banners
- Sidewalk graphics
- Directional signage
- Vehicle graphics